

SAFETY DATA SHEET

Classified in accordance 29 CFR 1910.1200

1. Identification

Product identifier: RELIABLE POWER BLASTER HIGH PERFORMANCE PENETRATING CATALYST

Other means of identification

SDS number: RE1000001360

Recommended restrictions

Recommended use: Lubricant

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: RELIABLE PRODUCTS
Address: 639 FITCH STREET
ONEIDA, NY 13421
US
Telephone: 315-363-9202

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Aspiration Hazard Category 1

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.
May be fatal if swallowed and enters airways.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting.

Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Distillates (petroleum), hydrotreated light	64742-47-8	50 - <100%
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	20 - <50%
Propane	74-98-6	5 - <10%
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - <5%
Proprietary		1 - <5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments: The components are not hazardous or are below required disclosure limits.

The exact concentration has been withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

Inhalation:	Move to fresh air.
Skin Contact:	Wash skin thoroughly with soap and water. Get medical attention if symptoms occur.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.
Ingestion:	Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Personal Protection for First-aid Responders:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

Accidental release measures: Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation): No data available.

Safe handling advice: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Contact avoidance measures: No data available.

Storage

Safe storage conditions: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 3

Safe packaging materials: No data available.

Storage Temperature: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Distillates (petroleum), hydrotreated light	REL	100 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated light - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values, as amended
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), hydrotreated heavy naphthenic	TWA	400 ppm 1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic	Ceiling	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated heavy naphthenic - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), hydrotreated heavy naphthenic	REL	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Propane	REL	1,000 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Ethanol, 2-(2-butoxyethoxy)- - Inhalable fraction and vapor.	TWA	10 ppm	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO - Mist.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic	TWA	400 ppm 1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic - Mist.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended

Distillates, Petroleum, Hydrotreated Light Naphthenic	Ceil_Time	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), solvent-dewaxed heavy paraffinic	TWA	400 ppm 1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Mist.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Ceil_Time	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated light paraffinic - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated light paraffinic - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), solvent-dewaxed light paraffinic - Mist.	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), solvent-dewaxed light paraffinic - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended

Exposure guidelines

Distillates (petroleum), hydrotreated light	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.
	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

No data available.

Skin and Body Protection:

Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. When using do not smoke.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor Threshold:	No data available.
pH:	No data available.
Freezing point:	No data available.
Boiling Point:	No data available.
Flash Point:	Estimated -104.4 °C
Evaporation Rate:	No data available.
Flammability (solid, gas):	No data available.
Explosive limit - upper (%):	Estimated 9.5 %(V)
Explosive limit - lower (%):	Estimated 2.2 %(V)
Vapor pressure:	No data available.
Vapor density (air=1):	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility in Water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Self Ignition Temperature:	No data available.
Decomposition Temperature:	No data available.
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	No data available.
Oxidizing properties:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Components:

Distillates (petroleum), hydrotreated light	NOAEL (Rat(Female, Male), Inhalation): ≥ 24 mg/m ³ Inhalation Experimental result, Key study NOAEL (Rat(Female), Oral, 70 - 147 d): 750 mg/kg Oral Experimental result, Key study
Distillates (petroleum), hydrotreated heavy naphthenic	NOAEL (Rat(Female, Male), Inhalation): > 980 mg/m ³ Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 13 Weeks): $\geq 2,000$ mg/kg Dermal Experimental result, Key study
Propane	NOAEL (Rat(Female, Male), Inhalation, ≥ 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, ≥ 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)-	NOAEL (Rat(Female, Male), Inhalation, 90 - 120 d): 14 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Oral, 90 d): 250 mg/kg Oral Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 13 Weeks): $> 2,000$ mg/kg Dermal Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Components:

Distillates (petroleum), hydrotreated light	in vivo (Rabbit): Not irritant
Distillates (petroleum), hydrotreated heavy naphthenic	in vivo (Rabbit): Not irritant
Ethanol, 2-(2-butoxyethoxy)-	in vivo (Rabbit): Not irritant
Proprietary	Not classified as an Irritant

Serious Eye Damage/Eye Irritation

Product: No data available.

Components:

Distillates (petroleum),
hydrotreated light Rabbit, 24 - 72 hrs: Not irritating

Distillates (petroleum),
hydrotreated heavy
naphthenic Rabbit, 48 hrs: Not irritating

Ethanol, 2-(2-
butoxyethoxy)- Rabbit, 24 - 72 hrs: Highly irritating

Respiratory or Skin Sensitization

Product: No data available.

Components:

Distillates (petroleum),
hydrotreated light Skin sensitization:, in vivo (Guinea pig): Non sensitising

Distillates (petroleum),
hydrotreated heavy
naphthenic Skin sensitization:, in vivo (Guinea pig): Non sensitising

Ethanol, 2-(2-
butoxyethoxy)- Skin sensitization:, in vivo (Guinea pig): Non sensitising

Proprietary Not sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Components:

Distillates (petroleum),
hydrotreated light May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic LL 50 (Pimephales promelas, 96 h): > 100 mg/l Experimental result, Key study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Ethanol, 2-(2-butoxyethoxy)- LC 50 (Pimephales promelas, 96 h): 2,400 mg/l Experimental result, Supporting study

Proprietary LC 50 (96 h): > 100 mg/l

Aquatic Invertebrates

Product: No data available.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Experimental result, Key study
NOAEL (Daphnia magna, 48 h): >= 10,000 mg/l Experimental result, Key study

Ethanol, 2-(2-butoxyethoxy)- LC 50 (Daphnia magna, 48 h): +/- 1,743 mg/l QSAR QSAR, Supporting study

Proprietary EC 50 (48 h): > 100 mg/l

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Components:

Distillates (petroleum), hydrotreated light NOAEL (Oncorhynchus mykiss): 0.098 mg/l QSAR QSAR, Key study

Distillates (petroleum), hydrotreated heavy naphthenic NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic NOAEL (Daphnia magna): 10 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product: No data available.

Components:

Proprietary EC 50 (72 h): > 100 mg/l
NOEC (72 h): > 100 mg/l

Persistence and Degradability

Biodegradation

Product: No data available.

Components:

Distillates (petroleum), hydrotreated light	61 % Detected in water. Experimental result, Supporting study
Distillates (petroleum), hydrotreated heavy naphthenic	31 % (28 d) Detected in water. Read-across based on grouping of substances (category approach), Supporting study 2 - 4 % (28 d) Detected in water. Experimental result, Supporting study
Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Ethanol, 2-(2-butoxyethoxy)-	85 % (28 d) Detected in water. Experimental result, Key study
Proprietary	55 % (28 d) Not readily degradable.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Components:

Proprietary Log Kow: > 9.4 (Measured)

Mobility in soil:

No data available.

Components:

Distillates (petroleum), hydrotreated light	No data available.
Distillates (petroleum), hydrotreated heavy naphthenic	No data available.
Propane	No data available.
Ethanol, 2-(2-butoxyethoxy)-	No data available.
Proprietary	No data available.

Other adverse effects:

No data available.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	—
EmS No.:	
Packing Group:	II
Special precautions for user:	Not regulated.

IATA

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	—
Packing Group:	—
Special precautions for user:	Not regulated.
Other information	
Passenger and cargo aircraft:	Allowed. 203
Cargo aircraft only:	Allowed. 203

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2
Label(s):	—
EmS No.:	
Packing Group:	—
Special precautions for user:	Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended
None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity

Distillates (petroleum), hydrotreated light
UNLISTED HAZARDOUS WASTES CHARACTERISTIC OF IGNITABILITY
GLYCOL ETHERS

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable aerosol, Aspiration Hazard

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

Chemical Identity

Ethanol, 2-(2-butoxyethoxy)-

% by weight

1.0%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Distillates (petroleum), hydrotreated light
Distillates (petroleum), hydrotreated heavy naphthenic
Propane
Ethanol, 2-(2-butoxyethoxy)-
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO
Distillates, Petroleum, Hydrotreated Light Naphthenic
Distillates (petroleum), solvent-dewaxed heavy paraffinic
Distillates (petroleum), hydrotreated light paraffinic
Distillates (petroleum), solvent-dewaxed light paraffinic

US. Massachusetts RTK - Substance List

Chemical Identity

Distillates, Petroleum, Hydrotreated Light Naphthenic
Distillates (petroleum), hydrotreated light paraffinic
Distillates (petroleum), solvent-dewaxed light paraffinic

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Distillates (petroleum), hydrotreated light
Distillates (petroleum), hydrotreated heavy naphthenic
Propane
Ethanol, 2-(2-butoxyethoxy)-

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Distillates (petroleum), hydrotreated light

Stockholm convention

Distillates (petroleum), hydrotreated light

Rotterdam convention

Distillates (petroleum), hydrotreated light

Kyoto protocol

Inventory Status:

EINECS, ELINCS or NLP	Not in compliance with the inventory.
Japan (ENCS) List	Not in compliance with the inventory.
China Inv. Existing Chemical Substances	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI)	Not in compliance with the inventory.
Canada NDSL Inventory	Not in compliance with the inventory.
Japan ISHL Listing	Not in compliance with the inventory.
Japan Pharmacopoeia Listing	Not in compliance with the inventory.
Mexico INSQ	Not in compliance with the inventory.
Ontario Inventory	Not in compliance with the inventory.
Australia AICS	On or in compliance with the inventory
Canada DSL Inventory List	On or in compliance with the inventory
New Zealand Inventory of Chemicals	On or in compliance with the inventory
Philippines PICCS	On or in compliance with the inventory
Taiwan Chemical Substance Inventory	On or in compliance with the inventory
US TSCA Inventory	On or in compliance with the inventory

16. Other information, including date of preparation or last revision

Issue Date: 09/01/2020

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.